



TIMIDECAPA – Mass Paint Stripper

DESCRIPTION

The removal operation of old paint can be extremely difficult and slow when using mechanical tools, either due to the surface configuration or the several coats and the hardness of the old paint. The use of **Timidecapa** makes the stripping easier because it attacks the coating, blistering it and detaching it from the surface.

PROPERTIES

- Easy to apply, without sagging even on vertical surfaces
- Strong stripping action over almost all types of paints

APPLICATION DATA

SURFACE PREPARATION

Metal surfaces – Apply **Timidecapa** directly over the old paint.

Other surfaces – It is necessary carry out trials for two reasons:

- Surfaces sensitive to solvents: **Timidecapa** may cause damage.
- Wood or porous surfaces: **Timidecapa** can penetrate deeply and may be difficult to remove. An incomplete removal can affect the adherence of the new paint system and cause staining which will affect the final appearance.

APPLICATION METHOD

Brush

THINNING

Product ready to use

APPLICATION

Apply a thick and uniform coat with a brush over the paint to be removed. Leave for 5 to 10 minutes. With the aid of a spatula remove the old paint that has lifted. Repeat the operation until completely removed. Wash the surface with a suitable cleaning solvent.

UTENSILS/TOOLS CLEANING

The utensils/tools must be cleaned with **Diluyente Celuloso** immediately after the application.

ENVIRONMENTAL CONDITIONS DURING APPLICATION

Ambient Temperature

$\geq 5\text{ }^{\circ}\text{C}$

Relative Humidity

$\leq 80\%$

Surface Temperature

2 to 3 $^{\circ}\text{C}$ above dew point

SHELF LIFE

When stored inside in original containers and sheltered from sunlight and cold at temperatures between 5 and 40 $^{\circ}\text{C}$, the product has a shelf life of 2 years after its date of manufacture.

This technical data sheet is merely of an advisory nature, based on current technical know-how, for guidance, and may be changed without prior notice. As the conditions are beyond our control, the company cannot under any circumstances be held responsible for the obtained final results in its use.



TIMIDECAPA – Mass Paint Stripper

OBSERVATIONS

- 1- **Timidecapa** contains very volatile solvents which can cause a high pressure in the interior of the can. Open the cans carefully to avoid problems with the lid.
- 2- Due to the very high strength of solvents used in **Timidecapa** care must be taken to avoid skin contact. If this occurs, wash the affected area only with soap and water.

HEALTH, SAFETY AND ENVIRONMENT

In general, avoid contact with eyes and skin; gloves, goggles and appropriate clothing must be worn. Keep out of the reach of children. Use only in well ventilated areas. Do not empty into drains. Keep the container properly sealed and stored in the correct place. Take correct measures when transporting the product; Prevent any accident or incident that may occur during transportation, in particular the rupture or deterioration of the packaging. Ensure that the container is correctly stacked in a safe area. Do not store or use the product in extreme temperature conditions always between 5 and 40 °C. Always take account of the appropriate legislation relating to the Environment, Hygiene, Health and Safety at Work. For more information it is essential to read the label on the container and the product Material Safe Data Sheet.

This technical data sheet is merely of an advisory nature, based on current technical know-how, for guidance, and may be changed without prior notice. As the conditions are beyond our control, the company cannot under any circumstances be held responsible for the obtained final results in its use.